

CircuFlow™ 5208 Series of Intermittent Pneumatic Compression (IPC) Pumps

The CircuFlow™ 5208 Intermittent Pneumatic Compression (IPC) Pump Model allows patients the freedom to treat chronic venous and lymphatic disorders in the comfort of their own homes. Using intermittent gradient sequential pressure applied through multi-chambered garments, the CircuFlow™ 5208 increases blood flow and provides extracellular fluid clearances. The device's 4"x1" digital LCD screen provides easy access to essential set up information and real-time pressure readings.

The CircuFlow™ 5208 offers two sub-therapy modes:

- **Uncorking Mode** which mimics the process of manual lymphatic drainage.
- **Focus Mode** which concentrates on areas of the limb most affected by Lymphedema Fibrosis.

Key Features:

- FDA and CE Approved
- 8 individual pressure adjustable chambers
- Adjustable cycle time, distal to proximal; 20 – 240 seconds
- Dual operation modes: gradient mode or pressure mode
- Customizable pressure from 20 – 120 mmHg
- Smart pressure monitoring: preventing pressure tunneling due to operator set up error
- Ability to adjust or skip individual chamber pressures
- Automatic vacuum that drains the air from the garments for fast and easy removal after therapy
- Optional uncorking mode and focus mode





CircuFlow™ 5208 Snap Connector



8 Chamber Leg Garments

Specifications

Dimensions: 11.5" (W) x 10" (D) x 4" (H)

Weight: 12 lbs.

Inflation Cycle: Adjustable 2.5 – 30 seconds per chamber

Deflation Cycle: 12 seconds

Cycle Time: Adjustable 20 – 240 seconds

Therapy Time: Adjustable 15 – 180 minutes

End Therapy Vacuum Time: 60 seconds

Electrical: 5208: 120VAC, 60Hz, 100VA MAX

5228: 220VAC, 50Hz, 100VA MAX

Fuse Rated: 250VAC, 1.0AMP, SLO-BLO

Applied Part: TYPE B

Protection Against Electric Shock: CLASS I

Operation Mode: Continuous operation with intermittent loading